

# 裸板系列结构尺寸表

型号	输入电压	输出功率(W)	输出电压/电流(V/A)	外型尺寸(mm)	安装尺寸(mm)	接线方式	备注
JPB5-1	A <sub>12</sub>	5	5/1,12/0.4,24/0.2	40×30×18		单边直插式	无EMI
JPB5B-1	A <sub>12</sub>	5	5/1,12/0.4,24/0.2	50×32×18		单边直插式	
JPB10-1	A <sub>12</sub>	10	5/2,12/0.8,24/0.4	66×31×25	59×25	单边8.5座	无EMI
JPB10-2	A <sub>12</sub>	10	5/1,-5/0.1	66×31×25	59×25	单边8.5座	无EMI
JPB10-3	A <sub>12</sub>	10	5/1,±5/0.1	66×31×25	59×25	单边8.5座	无EMI
JPB10A-1	A <sub>12</sub>	10	5/2,12/0.8,24/0.4	76×35×25	68×27	双边3.96针	
JPB10A-2	A <sub>12</sub>	10	5/1,12/0.2	76×35×25	68×37	双边3.96针	
JPB10L-1	A <sub>12</sub>	10	5/2,12/0.8,24/0.4	79×52×15	72×45	单边5.0座	超薄
JPB10L-2	A <sub>2</sub>	10	5/1,12/0.2	95×53×15	88×45	单边5.0座	超薄
JPB10L-4	A <sub>2</sub>	10	3.3/1,5/0.8,12/0.1,30/0.01	100×65×15	93×55	双边3.96针	超薄
JPB15-1	A <sub>12</sub>	15	5/3,12/1,15/1	80×52×25	72×44	双边3.96针	
JPB15A	A <sub>12</sub>	15	5/3,12/1,15/1	105×47×25	95×37	双边3.96针	
JPB15B	A <sub>12</sub>	15	5/3,12/1.2,15/1	105×47×25	95×37	双边3.96针	
JPB15C	A <sub>12</sub>	15	5/3,12/1.2,15/1	105×47×25	95×37	单边3.96针	
JPB15D	A <sub>12</sub>	15	5/3,12/1.2,15/1	105×50×30	97×39	双边3.96针	
JPB15A-2	A <sub>2</sub>	15	5/3,12/1.2 5/2,12/0.4	110×40×30	120×32	双边3.96针	
JPB15XA	A <sub>2</sub>	15	5/3,12/1.2 5/1,12/0.4	140×90×20	125×80	双边3.96针	
JPB20-1	A <sub>2</sub>	25	5/2,12/0.4,12/1.6	115×30×25	95×53	双边3.96针	
JPB20-2	A <sub>2</sub>	25	5/1,12/0.4	115×30×25	80×80	双边3.96针	
JPB20-3	A <sub>2</sub>	25	5/2,12/0.5,-12/0.2	90×90×30	80×80	双边3.96针	
JPB25-1	A <sub>2</sub>	25	5/1,12/1,12/2	107×60×30	95×53	双边3.96针	
JPB25-2	A <sub>2</sub>	25	24/0.7,12/0.4,16/0.15	107×60×30	95×53	双边3.96针	
JPB25-3	A <sub>2</sub>	25	5/2,±12/0.3	107×60×30	95×53	双边3.96针	
JPB25JD	A <sub>2</sub>	25	5/3,12/0.5,24/1	107×60×30	95×53	双边3.96针	带继电器
JPB3030	A <sub>2</sub>	35	5/2,±12/0.3	127×76×30	116×65	双边3.96针	
JPB45HZ	A <sub>2</sub>	45	54/8	150×60×40	140×52	双边3.96针	
JPB1050	A <sub>2</sub>	50	13.8/3	110×70×30	100×60	双边3.96针	
JPB1050A	A <sub>2</sub>	50	15.4/3	127×76×30	116×66	双边3.96针	
JPB2050	A <sub>2</sub>	50	5/5, 3, 3.3/5	127×76×30	116×66	双边3.96针	
JPB3050	A <sub>2</sub>	50	5/3,24/1,-5/0.2	127×76×30	116×66	双边3.96针	
JPB3050Y	A <sub>2</sub>	50	24/2,5/1,-5/0.3	144×76×30	132×66	双边3.96针	耐压4000V
JPB50-5G	A <sub>2</sub>	50	6.3V-6V,19V-15V	160×100×45	150×90	单边3.96针	